UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/938,093	08/23/2001	David J. Flynn	21220/04089 (GR201 SF054)	9854

24024 7590 11/03/2004		EXAMINER	
CALFEE HALTER & GRISWOLD, LLP		MISLEH, JUSTIN P	
800 SUPERIOR AVENUE			
SUITE 1400		ART UNIT	PAPER NUMBER
CLEVELAND, OH 44114		2612	

DATE MAILED: 11/03/2004

Please find below and/or attached an Office communication concerning this application or proceeding.

		Application No.	Applicant(s)
Office Action Summary		09/938,093	FLYNN, DAVID J.
		Examiner	Art Unit
		Justin P Misleh	2612

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE _3_ MONTH(S) FROM
THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☐ Responsive to communication(s) filed on _____ .

2a)☐ This action is **FINAL**. 2b)☒ This action is non-final.

3)☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4)☒ Claim(s) _1 - 20_ is/are pending in the application.

    4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5)☐ Claim(s) _____ is/are allowed.

6)☒ Claim(s) _1 - 11, 19, and 20_ is/are rejected.

7)☒ Claim(s) _11 - 18_ is/are objected to.

8)☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9)☒ The specification is objected to by the Examiner.

10)☒ The drawing(s) filed on _23 August 2001_ is/are: a)☒ accepted or b)☐ objected to by the Examiner.

    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

    Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

11)☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12)☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

    a)☐ All b)☐ Some * c)☐ None of:

        1.☐ Certified copies of the priority documents have been received.

        2.☐ Certified copies of the priority documents have been received in Application No. _____ .

        3.☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

    * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1)☒ Notice of References Cited (PTO-892)

2)☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)

3)☐ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
    Paper No(s)/Mail Date _____ .

4)☐ Interview Summary (PTO-413)
    Paper No(s)/Mail Date. _____ .

5)☐ Notice of Informal Patent Application (PTO-152)

6)☐ Other: _____ .

DETAILED ACTION

Specification

1.   Applicant is reminded of the proper language and format for an abstract of the disclosure.

The abstract should be in narrative form and generally limited to a single paragraph on a

separate sheet within the range of 50 to 150 words. It is important that the abstract not exceed

150 words in length since the space provided for the abstract on the computer tape used by the

printer is limited. **The form and legal phraseology often used in patent claims, such as**

"means", "said" and "disclosed," should be avoided. The abstract should describe the

disclosure sufficiently to assist readers in deciding whether there is a need for consulting the full

patent text for details.

The language should be clear and concise and should not repeat information given in the

title. It should avoid using phrases which can be implied, such as, "The disclosure concerns,"

"The disclosure defined by this invention," "The disclosure describes," etc.

2.   The title of the invention is not descriptive. A new title is required that is clearly

indicative of the invention to which the claims are directed.

3.   The disclosure is objected to because of the following informalities: The difference

between two separate reference sign descriptions is unclear.

More specifically, reference sign 42 and reference sign 40 point to separate items in

figure 2; however, in the specification, reference sign 40 is labeled as a CCD image detector and

reference sign 42 is also labeled as a CCD image detector. The Examiner suggests amending the

specification, at all appropriate instances, to clearly distinguish between each reference sign as

they are distinguished in figure 2.

Appropriate correction is required.

Drawings

4.   Figure 1 should be designated by a legend such as --Prior Art-- because only that which is

old is illustrated. See MPEP § 608.02(g).

Corrected drawings in compliance with 37 CFR 1.121(d) are required in reply to the

Office action to avoid abandonment of the application. The replacement sheet(s) should be

labeled "Replacement Sheet" in the page header (as per 37 CFR 1.121(d)) so as not to obstruct

any portion of the drawing figures. If the changes are not accepted by the Examiner, the

Applicant will be notified and informed of any required corrective action in the next Office

action. The objection to the drawings will not be held in abeyance.

Claim Objections

5.   **Claim 11** is objected to because of the following informalities: lack of clarity and

precision.

In regards to step (b), the Applicant states "a burst of fist clock pulses wherein each said

pulse controls", and likewise, in regards to step (c), the Applicant states "a burst of second clock

pulses wherein each said pulse controls". Due to the fact that in both steps (b) and (c), the

Applicant simply states "said pulse controls" demonstrates a lack of clarity and precision,

because the Applicant fails to specify which "said pulse controls" the Applicant intended to refer

to. To alleviate the problem, the Examiner suggests changing "said pulse controls" to "said first

pulse controls" and "said second pulse controls", respectively. For the purposes of examination,

the Examiner will interpret Claim 11 according to the above-stated suggestions.

Appropriate correction is required.

Claim Rejections - 35 USC § 102

6.   The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the

basis for the rejections under this section made in this Office action:

> A person shall be entitled to a patent unless –
>
> (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on
> sale in this country, more than one year prior to the date of application for patent in the United States.

7.   **Claims 1, 2, 4, 5, 7 – 10, 11, and 20** are rejected under 35 U.S.C. 102(b) as being

anticipated by David et al.

8.   For **Claim 1**, David et al. disclose, as shown in figures 7 – 11 and as stated in columns 8

(lines 54 – 67), 9 (lines 1 – 11), and 11 (lines 10 – 42), a charge coupled device (CCD) image

detector comprising:

an image area (500) of an array of rows of gates, each gate of said image area array

being operative to collect and store a charge content representative of a picture element (pixel) of

an image, said rows of gates of the image area being operative concurrently by a first clock

signal ($\emptyset i$) to transfer in parallel the charge contents of the gates of each row to the gates of an

adjacent row in a predetermined direction through said image area;

a storage area (600/700) of array of rows of gates, each gate of said storage area array

being operative to store a charge content, said rows of gates of the storage area being operative

concurrently by a second clock signal (Øs) to transfer in parallel the charge contents of the gates

of each row to the gates of an adjacent row in the predetermined direction through said storage

area, said storage area array of rows (600/700) disposed in said CCD detector such that a first

row of said image area array of rows (bottom-most row closest to the storage area 600/700) is

adjacent a last row of said storage area array of rows (top-most row closest to the image area

500) to accommodate a transfer in parallel of the charge contents of the gates of said first row of

the image area to the gates of said last row of the storage area (the solid single direction

directional arrows are the direction in which charge travels), wherein the image and storage areas

are operative by the first and second clock signals, respectively, to transfer the charge contents of

the rows of the image area array to rows of the storage area array (See figure 9 and column 9,

lines 1 – 11);

a buffer area (610/710) of an array of rows of gates, each gate of said buffer area array

being operative to store a charge content, said rows of gates of the buffer area being operative

concurrently by a third clock signal (Øb) to transfer in parallel the charge contents of the gates of

each row to the gates of an adjacent row in the predetermined direction through said buffer area,

said buffer area array of rows disposed in said CCD detector such that a first row of said storage

area array of rows (bottom-most row closest to the buffer area 610/710) is adjacent a last row of

said buffer area array (top-most row closest to the storage area 600/700) of rows to accommodate

a transfer in parallel of the charge contents of the gates of said first row of the storage area to the

gates of said last row of the buffer area, wherein the storage and buffer areas are operative by the

second and third clock signals, respectively, to transfer the charge contents of the rows of the

storage area array to rows of the buffer area array (See figure 9 and column 9, lines 1 – 11); and

a readout register (340) of a row of gates, each gate of said readout register being

operative to store a charge content, said readout register disposed in said CCD detector such that

a first row of said buffer area array (bottom-most row closest to the readout register 340) of rows

is adjacent the row of said readout register (340) to accommodate a transfer in parallel of the

charge contents of the gates of said first row of the buffer area to the gates of said readout

register as controlled solely by the third clock signal (the clock signals operate independently),

said row of gates of the readout register being operative concurrently by a fourth clock signal

($\emptyset$h) to transfer serially the charge contents of the gates thereof through said register in a

predetermined direction to an output signal line (350).

9.   As for **Claim 2**, David et al. disclose, as shown in figures 7 and 10, the CCD image

detector of Claim 1 wherein the number of rows (1035 – rows) of the image area array (500) is

equal to the composite number of rows of the storage area array (600/700 – 748 rows) and buffer

area array (610/710 – 287 rows).

10.   As for **Claim 4**, David et al. disclose, as stated in columns 8 (lines 59 – 65) and 11 (lines

25 – 31), that the number of rows in the buffer area (610/710) is purposely set as a fraction of the

number of rows of the image area (500), so as to achieve the advantages of a reduction in

"thermal noise" and increased "bandwidth"; therefore, David et al. also disclose the CCD image

detector of Claim 1 wherein the number of rows of the buffer area array (610/710) is equal to the

number of a designated band of rows of the image area array.

11.   As for **Claim 5**, although it is not shown, it is inherent to David et al. for David et al. to

provide the CCD image detector of Claim 1 comprising a timing controller for controlling the

operation of the first, second, third and fourth clock signals. David et al. would not be able to provide the clock signals (Øi; Øs; Øb; Øh) if a timing controller were not present therein.

12.   As for **Claim 7**, David et al. disclose, as shown in figure 9, the CCD image detector of Claim 5 wherein the timing controller operates the first, second, third and fourth clock signals (Øi; Øs; Øb; Øh) in a predetermined sequence to effect a readout of the charge content of a plurality of bands (one band of a plurality of bands corresponds the "previous active field period" and another band of the plurality of bands corresponds to the "field period") of rows of gates.

13.   As for **Claim 8**, David et al. disclose, as shown in figures 10 and 11, the CCD image detector of Claim 5 wherein the timing controller operates the first, second, third and fourth clock signals (Øi; Øs; Øb; Øh) in a predetermined sequence to effect a readout of the charge content of an image frame ("frame transfer").

14.   As for **Claim 9**, David et al. disclose, as shown in figure 9 and as stated in column 9 (lines 4 – 9), the CCD image detector of Claim 5 wherein timing controller is operative to:

(1 – see figure 9f) control the first, second and third clock signals (Øi; Øs; Øb) concurrently to transfer the charge contents of the rows of the image area array to rows of the storage area array (600/700) and the buffer area array (610/710),

(2 – see figure 9b) control the second and third clock signals (Øs; Øb) concurrently to transfer the charge contents of the rows of the storage area array (600/700) to rows of the buffer area array (610/710),

(3 – see figure 9d) control the third clock signal (Øb) to transfer in parallel the charge contents of the last row of the buffer area (610/710) to the readout register (340), and

(4 – see column 9, lines 4 – 9) control the fourth clock signal (Øh) to transfer serially the

charge contents of the gates of the readout register (340) through the register in a predetermined

direction to the output signal line (350).

15.   As for **Claim 10**, David et al. disclose, as shown in figures 7, 8, and 9 and as stated in

column 9 (lines 4 – 9), the CCD image detector of Claim 5 wherein the timing controller controls

solely the third clock signal (Øb) to transfer the charge contents of the buffer area array

(610/710) of rows to the read out register (340).

16.   For **Claim 11** (please see objection above), David et al. disclose, as shown in figures 7 –

11 and as stated in columns 8 (lines 54 – 67), 9 (lines 1 – 11), and 11 (lines 10 – 42), method of

operating a charge coupled device (CCD) as an image detector comprising the steps of:

(a – see figures 9a – 9c) collecting and storing charge content in gates of an image area

array (500) of rows of gates for a predetermined period of time, said charge content of said gates

of said image area array representative of a picture elements (pixels) of an image frame;

(b – see figures 9d – 9f) transferring the stored charge contents of the image area array

(500) to a storage area array (600/700) of rows of gates controlled by a burst of first clock pulses

(Øi – see column 8, lines 54 – 60, and column 10, lines 16 – 20) wherein each said [first] pulse

controls the transfers in parallel of the stored charge contents of gates between adjacent rows

through the image and storage areas in a predetermined direction (the solid single direction

directional arrows are the direction in which charge travels);

(c – see figures 9f and 9g) transferring the charge contents of a predetermined number of

adjacent rows of the storage area array (600/700) to a like number of adjacent rows of a buffer

area array (610/710) of rows of gates controlled by a burst of second clock pulses (Øs – see

column 10, lines 32 – 40) wherein each said [second] pulse controls the transfers in parallel of

the stored charge contents of gates between adjacent rows through the storage and buffer areas in

the predetermined direction (the solid single direction directional arrows are the direction in

which charge travels);

(d – see figures 9a – 9c) transferring in parallel the charge contents of adjacent rows

through the buffer area array (610/710) in the predetermined direction by a pulse of a third clock

(Øb) so that the charge contents of a last row of gates of the buffer area array are transferred in

parallel to a row of gates in a readout register (340);

(e – see column 9, lines 4 – 9) shifting out the charge contents of the gates of the readout

register serially to an output (350) of the CCD as controlled by the pulses of a fourth clock (Øh);

(f) thereafter, repeating steps (d) and (e) for each row of the predetermined number of

adjacent rows of stored charge content of the buffer area array transferred from the storage area

array in step (d); and

(g) repeating steps (c)-(f) for each predetermined number of adjacent rows of a set of

predetermined number of adjacent rows of the storage area array (Steps f and g correspond to a

frame transfer method of operating, which is shown in figures 10 and 11 of David et al.).

17.   As for **Claim 20**, David et al. disclose, as shown in figures 9 and 10, a "previous field"

and a current "field"; therefore, David et al. disclose the method of Claim 11 including the step

of repeating steps of (a) through (g) periodically.

Claim Rejections - 35 USC § 103

18.   The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all

obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in
> section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are
> such that the subject matter as a whole would have been obvious at the time the invention was made to a person
> having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the
> manner in which the invention was made.

19.   **Claims 3, 6, and 19** are rejected under 35 U.S.C. 103(a) as being unpatentable over

David et al.

20.   As for **Claim 3**, David et al. disclose, as stated in columns 8 (lines 59 – 65) and 11 (lines

25 – 31), that the number of rows in the buffer area (610/710) is purposely set as a fraction of the

number of rows of the image area (500), so as to achieve the advantages of a reduction in

"thermal noise" and increased "bandwidth"; however, David et al. does not specify that the

number of rows in the buffer area is equal to the square root of the number of rows of the image

area rounded up to the nearest integer.

Since setting the number of rows in the buffer area to a specific fraction of the number of

rows in the image area is taught by David et al., at the time the invention was made, it would

have obvious to one with ordinary skill in the art to also have set the number rows in the buffer

area to the square root of the number of rows of the image area rounded up to the nearest integer.

At the time the invention was made, one with ordinary skill in the art would have been motivated

to set the number of rows in the buffer area to the square root of the number of rows of the image

area rounded up to the nearest integer for the advantage of reducing the "thermal noise" and

increasing the "bandwidth" of image data.

21.   As for **Claims 6 and 19,** while David et al. disclose operating the CCD image detector as

a frame transfer image detector, David et al. do not disclose purging the CCD image detector of

charge contents. However, **Official Notice** (See MPEP § 2144.03) is taken that both the

concepts and advantages of purging the CCD image detector of charge contents are well known

and expected in the art. At the time the invention was made, it would have been obvious to one

with ordinary skill in the art to have purged the CCD image detector of charge contents, so as to

reduce the occurrence of smearing.

Allowable Subject Matter

22.   Claims 12 – 18 are objected to as being dependent upon a rejected base claim, but would

be allowable if rewritten in independent form including all of the limitations of the base claim

and any intervening claims. The following is a statement of reasons for the indication of

allowable subject matter:

As for **Claims 12 and 15,** while the closest prior art teaches of providing a frame transfer

charge-coupled image sensor wherein the transfer rate between an image acquisition area and an

image storage is low to reduce thermal and fixed pattern noise, the closest prior art does not

teach or fairly suggest dividing the storage area array into a plurality of bands of rows wherein

each band of said plurality includes a predetermined number of adjacent rows of charge content

and then transferring the charge contents of a predetermined number of adjacent rows of the

storage area array to a like number of adjacent rows of a buffer area array of rows of until a first

band of charge content of said plurality of bands is transferred to the buffer area array.

Conclusion

23.   The prior art made of record and not relied upon is considered pertinent to applicant's

disclosure. The following is a brief description of the cited prior art as labeled on attached form

PTO-892:

o **Prior Art B** discloses, in the very least, as shown in figure 3, an image area array (24),

storage area array (26A), a buffer area array (26B), and a readout register (27).

Any inquiry concerning this communication or earlier communications from the

Examiner should be directed to Justin P Misleh whose telephone number is 703.305.8090. The

Examiner can normally be reached on Monday through Thursday from 7:30 AM to 5:30 PM and

on alternating Fridays from 7:30 AM to 4:30 PM.

If attempts to reach the Examiner by telephone are unsuccessful, the Examiner's

supervisor, Wendy R Garber can be reached on 703.305.4929. The fax phone number for the

organization where this application or proceeding is assigned is 703.872.9306.

Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published applications

may be obtained from either Private PAIR or Public PAIR. Status information for unpublished

applications is available through Private PAIR only. For more information about the PAIR

system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR

system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

JPM
October 21, 2004